



## Technical Bulletin 122 - New Condensing Tankless Venting Options

The purpose of this technical bulletin is to inform about the certification of M&G Duravent, Metal-Fab Low Profile terminations, and Royal low profile and concentric terminations with Rinnai Condensing Tankless Water Heaters. (See tables below for product compatibility)

### M&G Duravent

	Equivalent Length
45 degree elbow	3ft
90 degree elbow	6ft

The following Duravent products are approved for use with Rinnai water heaters:

- 3" diameter PPS (lengths and elbows)
- 3PPS-ADL, 3" Appliance Adapter
- 3PPS-HTPL, 3" Twin Pipe Termination
- 3PPS-VKL/VK-TCL, 3" Concentric Vertical Termination
- 3PPS-HKL, 3" Concentric Horizontal Termination

Duravent material compatible with:

- REU-KBD2530FFUD (RUC80i)
- REU-KBD2934FFUD (RUC90i)
- REU-KBD3237FFUD (RUC98i)
- REU-KBD3237FFUDC (C199i)
- REU-KBP3237FFUD (RUR98i)

### Metal-Fab

	Equivalent Length
3CGVRHK3 (2X4 Wall)	16ft*
3CGVRHK4 (2X6 Wall)	16ft*

\*Just the equivalency for the termination. The 90° elbow is equivalent to 6ft.

Metal-Fab material compatible with:

- REU-KBD2530FFUD (RUC80i)
- REU-KBD2934FFUD (RUC90i)
- REU-KBD3237FFUD (RUC98i)
- REU-KBD3237FFUDC (C199i)
- REU-KBP3237FFUD (RUR98i)
- REU-KCM2025FFU (RUCS65i)
- REU-KCM2528FFU (RUCS75i)

### Royal GVS-65 Vent Pipe

	Equivalent Length
52CVKGV6503 (Concentric Vent Termination Kit)	20ft
52SWVKGVS6503 (Low Profile Termination Kit)	5ft

Royal material compatible with:

- REU-KBD2530FFUD (RUC80i)
- REU-KBD2934FFUD (RUC90i)
- REU-KBD3237FFUD (RUC98i)
- REU-KBD3237FFUDC (C199i)
- REU-KBP3237FFUD (RUR98i)
- REU-KCM2025FFU (RUCS65i)
- REU-KCM2528FFU (RUCS75i)

Rinnai America Corporation • 103 International Drive, Peachtree City, GA 30269

Toll-Free: 1-800-621-9419 • Phone: 678-829-1700 • [www.rinnai.us](http://www.rinnai.us)

©2016 Rinnai America Corporation. Rinnai America Corporation continually updates materials, and as such, content is subject to change without notice. Local, state, provincial, federal and national fuel gas codes must be adhered to prior to and upon installation.