

Use your location on the map to correlate with legend for average ground water temperature in the U.S. and Canada. For Hawaii and Puerto Rico, use ground water temperature of 75° F / 23.9° C.

For Alaska, use ground water temperature range 35-42° F. / 1.7-5.6 ° C

SENSEI®RX Series Model: RX180IN BTU: 180,000	Ground Water Temperature (° F / ° C)	Max Flow Rate (GPM / LPM)	Simultaneous Shower Use
	35°F/1.7°C	4.1 / 15.6	
	37° F / 2.8° C	4.2/16.0	
	42°F/5.6°C	4.5 / 17.0	
100 100 100 100 mm	47° F / 8.3° C	4.8 / 18.2	
	52° F / 11.1° C	5.2/19.5	
	57°F/13.9°C	5.6 / 21.1	
	62° F / 16.7° C	6.0/22.9	<u> </u>
	67°F/19.4°C	6.6 / 25.0	2222
	72°F/22.2°C	7.3 / 27.6	2222
	77°F/25°C	8.2/30.9	22222

Note: Simultaneous shower use was rounded to the nearest whie number based on the following data:

Tank less set temperature of 120°F/49°C, mixed shower temperature of 105°F/40.6°C, ground water temperature as shown in the chart, and shower head flow rate of 2 gpm / 7.6 lpm.

Customer has the option of using the following appliances instead of a shower:

 $Residential\ grade\ clothes\ washing\ machine, hand\ sink\ or\ dishwasher.$

Shower heads will be as above. If custom shower fixtures i.e. body sprays, high flow rate rain heads are used, please contact Rinnai.